








































适配现场可接线接头	型号	订货号	特性描述	针脚排列图
M8x1 直线孔头 	SK3112-0/M10	10093000	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 螺钉连接 85°C, 60V, 4 A	
	SK4112-0/M10	10093001	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 螺钉连接 85°C, 60V, 4 A	
M8x1 直线针头 	SZ3112-0/M10	10093020	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 螺钉连接 85°C, 60V, 4 A	
	SZ4112-0/M10	10093021	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 螺钉连接 85°C, 60V, 4 A	
M8x1 直线孔头 	SK3112-0/M10/L	10093040	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	
	SK4112-0/M10/L	10093041	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	
M8x1 直线针头 	SZ3112-0/M10/L	10093060	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	
	SZ4112-0/M10/L	10093061	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	

适配现场可接线接头	型号	订货号	特性描述	针脚排列图
M8x1 直线孔头 	SLK3112-0/M10	10093010	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	
	SLK4112-0/M10	10093011	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	
M8x1 直线针头 	SLZ3112-0/M10	10093030	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	
	SLZ4112-0/M10	10093031	PA6+GF,黑色/铜锌合金 M10 电缆出线口 可连接的电缆外径范围:3.5-5 mm 焊接连接 85°C, 60V, 4 A	

适配现场可接线接头	型号	订货号	特性描述	针脚排列图
M12x1 直线孔头 	EK4111-0/7	10091005	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 250 V, 4 A	
	EK4111-0/9	10091006	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 250 V, 4 A	
	EK5111-0/7	10091007	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	EK5111-0/9	10091008	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	
M12x1 直角孔头 	ELK4111-0/7	10091015	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 250 V, 4 A	
	ELK4111-0/9	10091016	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 125 V, 4 A	
	ELK5111-0/7	10091017	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	ELK5111-0/9	10091018	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	
M12x1 直线孔头 	EK4114-0/7	10091040 10091040	PBT, 无色/PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 125 V, 4 A	
	EK4114-0/9	10091041	PBT, 无色/PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 250 V, 4 A	
	ELK5114-0/7	10091042	PBT, 无色/PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	ELK5114-0/9	10091043	PBT, 无色/PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	

适配现场可接线接头	型号	订货号	特性描述	针脚排列图
M12x1 直角孔头 	ELK4114-0/7	10091050	PBT, 无色/PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 250 V, 4 A	
	ELK4114-0/9	10091051	PBT, 无色/PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 250 V, 4 A	
	ELK5114-0/7	10091052	PBT, 无色/PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	ELK5114-0/9	10091053	PBT, 无色/PA, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	
M12x1 直线孔头 	ELK4112-0/7	10091000	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 250 V, 4 A	
	ELK4112-0/9	10091001	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 125 V, 4 A	
	ELK5112-0/7	10091002	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	ELK5112-0/9	10091003	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	
M12x1 直角孔头 	EK4112-0/7	10091010	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 125 V, 4 A	
	ELK4112-0/9	10091011	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 250 V, 4 A	
	ELK5112-0/7	10091012	PA6+GF, 黑色 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	ELK5112-0/9	10091013	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	

适配现场可接线接头	型号	订货号	特性描述	针脚排列图
M12x1 直线针头 	EZ4112-0/7	10091020	PA6+GF, 黑色/黄铜镀镍 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 250 V, 4 A	
	EZ4112-0/9	10091021	PA6+GF, 黑色/黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 250 V, 4 A	
	EZ5112-0/7	10091022	PA6+GF, 黑色/黄铜镀镍 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	EZ5112-0/9	10091023	PA6+GF, 黑色/黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	
M12x1 直角针头 	ELZ4112-0/7	10091030	PA6+GF, 黑色/黄铜镀镍 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 250 V, 4 A	
	EZ5128-0/9	10091031	PA6+GF, 黑色/黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 250 V, 4 A	
	EZ4138-0/9	10091032	PA6+GF, 黑色/黄铜镀镍 PG 7 电缆出线口 可连接的电缆外径范围: 4-6 mm 螺钉连接 85°C, 60 V, 4 A	
	EZ5128-0/9	10091033	PA6+GF, 黑色/黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 60 V, 4 A	

适配现场可接线接头	型号	订货号	特性描述	针脚排列图
M12x1 直线孔头/双电缆输出 	EK4111-1/11	10091100	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 2* (2.1-3或4-5)mm 螺钉连接 85°C, 125 V, 4 A	
	EK4112-1/11	10091101	PA6+GF, 黑色/黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 2* (2.1-3或4-5)mm 螺钉连接 85°C, 125 V, 4 A	
M12x1 直线针头/双电缆输出 	EZ4111-1/11	10091110	PA6+GF, 黑色 PG 9 电缆出线口 可连接的电缆外径范围: 2* (2.1-3或4-5)mm 螺钉连接 85°C, 125 V, 4 A	
	EZ4112-1/11	10091111	PA6+GF, 黑色/黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 2* (2.1-3或4-5)mm 螺钉连接 85°C, 125 V, 4 A	
M12x1 直线孔头/全金属屏蔽 	EK4138-0/9	10091220	黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 125 V, 4 A	
	EK5128-0/9	10091200	黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 125 V, 4 A	
M12x1 直线针头/全金属屏蔽 	EZ4138-0/9	10091230	黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 125 V, 4 A	
	EZ5128-0/9	10091210	黄铜镀镍 PG 9 电缆出线口 可连接的电缆外径范围: 6-8 mm 螺钉连接 85°C, 125 V, 4 A	